

## Swiss GriP<sup>®</sup> Non-Slip Spray

Solvent-based, single-component non-slip coating

400ml - covers up to 1.5sqm

Transparent. For interior and exterior applications



### Description

Swiss GriP NonSlip Spray increases traction on every slippery surface. The coating is based on a fast drying acrylic coating. It is the only fully UV-stable, transparent non-slip spray available. It can be applied on acrylics, tiles, ceramics, wood, metal and other correctly prepared surfaces.

Product Code: K 9750-001.000

### Features

- Single-component acrylic coating
- Transparent finish
- UV-stable, non-yellowing
- Easy to install and easy to renew
- Fast drying

### Uses

SWISS GriP NonSlip Spray can be used on showers, pool decks, yachts, stairs and other slippery surfaces. The product is suitable for interior and exterior use.

### Precautions And Limitations

Consult Safety Data Sheet as well as the safety information on the can before application. Use only in a well-ventilated area.

Wear respiratory protection and other personal protective equipment such as safety clothing, glasses and gloves.

VOC Level: EU (g/l): 731.9

CH (g/kg): 851

Do not apply in exterior situations when rain threatens. Practical spreading rates will vary depending on such factors as method and conditions of applications and surface roughness and porosity. Suitable for application over bare substrate and water based coatings. For further advice contact SWISS GriP Australia on (03) 7020 2041 or [info@swiss-grip.com.au](mailto:info@swiss-grip.com.au).

### Typical Properties

Gloss Level	Flat	Colour	Transparent
Safety	Before using, read and follow all label and Safety Data Sheet (SDS) precautions, including respiratory protection and other Personal Protective Equipment such as safety clothing, glasses and gloves. Use only in a well-ventilated area.		
V.O.C. Level	731.9 g/l	Number of Coats	2-4, cross-wise
Shelf Life	36 months in an unopened can when stored dry and not in direct sunlight. Temperature must be between 5 and 30 degrees Celsius.		

Typical Properties	Drying Time on a day of 21C and 60% Relative Humidity
Notes	Touch Dry: 15 minutes Dry to handle: 12 hours

Application Guide	
Surface Preparation	<p>Thoroughly clean area using GriP Intensive Cleaner or another alkaline based cleaner in conjunction with water and a stiff bristled brush removing all dirt, dust and unwanted materials etc. Wash clean until all foaming ceases using a hose or power washer. Allow to dry before applying SWISS GriP NonSlip.</p> <p>Ensure surface is thoroughly dry before application. Ensure that previous coating is firmly bound to the substrate before painting. All loose and flaking paint must be thoroughly removed prior to painting.</p>
Application Procedure and equipment	<p>Wear protective gloves/eye protection/face protection and a mask. Only apply in well ventilated areas, and open windows. Do not enter the area for 6 hours after application. Remove dirt, oil, grease and other surface contaminants. The surface must be clean and dry during application. Apply masking tape or paper on walls to protect from possible mist. The relative air humidity must be below 85% and temperature should be above 12 degrees Celsius.</p> <ul style="list-style-type: none"> <li>To allow the painting of straight lines, mark out surface area with chalk string then use an appropriate masking tape to outline the intended lines.</li> <li>Shake thoroughly for at least one minute. The rattle of the mixing ball needs to be heard. Remove the cap and check the spray nozzle. Shake regularly during application process.</li> <li>Hold the can approximately 20 – 25cm from the surface. The can should always remain in motion when spraying to avoid a build-up of material.</li> <li>Use a back and forward motion while remaining parallel with the surface and cover the full surface. Apply two up to four layers with a one minute interval to achieve the right coating thickness. Avoid heavy wet coats to minimise risk of runs</li> <li>When applying indoors, do not enter for one hour after the application.</li> </ul>
	<p>This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.</p>
Handling	As with any chemical, ingestion, inhalation and prolonged repeated skin contact should be avoided by good occupational practice. Always wash hands before smoking, eating, drinking or using the toilet.
Equipment cleaning	Turn the can upside down and spray until the jet clears. Any over spray maybe cleaned up with Mineral Turps.
Other	For detailed information refer to the current Safety Data Sheet available through customer service: <a href="mailto:info@swiss-grip.com.au">info@swiss-grip.com.au</a>
UN Number	1950

