

## Swiss GriP<sup>®</sup> Sopro – Primer / Sealer

Single component primer/sealer

### Description

Solvent-free, single-component synthetic sealer/primer for high- and variable-suction substrates. Use as a primer/sealer in combination with Swiss GriP<sup>®</sup> Non-Slip.

### Features

- One-component sealer and primer
- Solvent-free

### Benefits

- One coat coverage
- Easy to apply by
- For indoor and outdoor applications
- Over coatable: after 60 minutes 21°C

### Uses

Swiss GriP<sup>®</sup> Sopro optimises adhesion of the Swiss GriP Non-Slip coatings on all surfaces. Can be used on substrates such concrete, ceramics, natural stone, cast stone, terrazzo, etc. Do not use on substrates exposed to risk of rising damp. It also stabilises friable surfaces and binds loose particles.

### Precautions And Limitations

Read Data Sheet, Material Safety Data Sheet and any precautionary labels on containers.

Do not apply in exterior situations when rain threatens. Suitable for application over bare substrate and water based coatings. For further advice contact SWISS GriP<sup>®</sup> Australia on (03) 7020 2041 or [info@swissgrip.com.au](mailto:info@swissgrip.com.au).

### Typical Properties

Gloss Level	Semi-Gloss	Thinner	With water: 1-1
Colour	Blueish when liquid. Transparent when applied and dry		
Components	1	Number of Coats	1
Toxicity	No adverse health effects expected if the product is handled in accordance with the directions on the Safety Data Sheet	V.O.C. Level	N.A.
Shelf Life	Approx. 24 months, subject to cool storage in well-sealed containers. Protect from frost.		

<b>Application Guide</b>	
Surface Preparation	<p>All loose and flaking paint must be thoroughly removed prior to painting. Do not apply when rain threatens.</p> <p>Thoroughly clean floors using Swiss GriP® Intensive Cleaner or another alkaline based detergent. Use a lime scale remover for bathrooms. Use in conjunction with water and a stiff bristled brush removing all dirt, dust and unwanted materials etc. Wash clean until all foaming ceases using a hose or power washer. Allow to dry before applying Swiss GriP® Sopro.</p> <p>Ensure surface is thoroughly dry before application.</p>
Coverage	<p>Approx. 15 - 20 grams of the diluted mixture per square metre, depending on substrate suction, environmental conditions, and application temperature. Swiss GriP® Sopro should in any case be left to dry for no longer than eight hours.</p>
Application Procedure and equipment	<ul style="list-style-type: none"> <li>Stir or shake prior to use.</li> <li>Dilute with water on 1:1 ratio in a small cup or bucket.</li> <li>Avoid puddling and skinning when applying the primer</li> </ul> <p><b>Small areas (&lt; 15sqm):</b> Use a sponge or cloth. Pour a small amount of the mixture to the surface and use sponge to spread the mixture evenly over the surface.</p> <p><b>Large areas: (&gt; 15sqm):</b> Use a high quality microfibre mop. Pour a small amount of mixture to the surface and let the mop absorb the mixture. Pour more of the mixture if required. Spread the mixture evenly over the surface.</p> <ul style="list-style-type: none"> <li>Avoid puddling and skinning.</li> </ul> <p><b>Curing</b></p> <ul style="list-style-type: none"> <li>One hour for normal temperature range of 21°C and 50% relative humidity. Higher temperatures shorten and lower temperatures lengthen these times.</li> <li>Application of Swiss GriP® Non-Slip may resume immediately after the priming coat has dried. Threatened surface will somewhat tacky.</li> <li>Do not use detergents after applying Swiss GriP® Sopro.</li> <li>Do not use the Primer/Promoter towel after applying Swiss GriP Sopro when using the Swiss GriP® Non-Slip 1.2sqm Kit. Continue straight away with applying the Swiss GriP® Non-Slip Coating.</li> <li>Masking tape can be used after applying Swiss GriP® Sopro and it has dried sufficiently. Do not apply masking tape before applying Swiss GriP® Sopro.</li> </ul>
Disposal	<p>Properly emptied and cleaned containers may be handed over for recycling. For more information on responsible disposal of paint and packaging visit the Australian website at <a href="http://paintback.com.au">paintback.com.au</a> or in New Zealand at <a href="http://paintback.co.nz">paintback.co.nz</a></p>
Handling	<p>As with any chemical, ingestion, inhalation and prolonged repeated skin contact should be avoided by good occupational practice. Always wash hands before smoking, eating, drinking or using the toilet.</p>
Other	<p>For detailed information refer to the current Safety Data Sheet available through customer service: <a href="mailto:info@swissgrip.com.au">info@swissgrip.com.au</a></p>